



SPECIFICATIONS

as at 1 June 2012

1 TABLE OF CONTENTS

1	TABLE OF CONTENTS	1
2	BOX (WT) TRAILERS	2
2.1	WT TRAILER TOPS.....	2
2.1.1	TOOLBOX TOP.....	2
2.1.2	FIBREGLASS.....	2
2.1.3	FLAT LID.....	2
2.1.4	PANTEC.....	2
2.1.5	TOURNEAU COVER.....	2
2.1.6	TRADESMAN TOP.....	2
2.1.7	WELDED MESH CAGE.....	2
2.2	WT TRAILER TYPES.....	3
2.2.1	WT GENERAL PURPOSE.....	3
2.2.2	WT MEDIUM DUTY.....	4
2.2.3	WT HEAVY DUTY.....	5
2.2.4	WT EXTRA HEAVY DUTY.....	6
2.2.5	WT EXTRA HEAVY DUTY HIGHSIDES.....	7
2.2.6	WT HEAVY DUTY - GALVANISED.....	8
2.2.7	WT EXTRA HEAVY DUTY - GALVANISED.....	9
2.2.8	WT 2 T TANDEM TRAILER.....	10
2.2.9	WT 2.5 T TANDEM TRAILER.....	11
2.2.10	WT 3 T TANDEM TRAILER.....	12
2.2.11	WT 3.5 T TANDEM TRAILER.....	13
2.2.12	WT CAR CARRIER, 2 T - LD.....	14
2.2.13	WT CAR CARRIER, 2 T - TILT.....	15
2.2.14	WT CAR CARRIER HD, 2.5 T - TILT.....	16
2.2.15	WT CAR CARRIER HD, 3 T - TILT.....	17
2.2.16	WT CAR CARRIER HD, 3.5 T - TILT.....	18
2.2.17	WT OFF ROAD TOURER.....	19
2.2.18	WT OFF ROAD GRAND TOURER.....	20
2.2.19	WT GOLF BUGGY, OPEN.....	21
2.2.20	WT GOLF BUGGY, ENCLOSED.....	22
2.2.21	WT MOTORBIKE TRAILER.....	23
2.2.22	WT INTEGRAL PANTEC, 1200 mm HIGH, SINGLE AXLE.....	24
2.2.23	WT INTEGRAL PANTEC, 1500 mm HIGH, SINGLE AXLE.....	25
2.2.24	WT INTEGRAL PANTEC, 2 T – TANDEM AXLE.....	26
2.2.25	WT INTEGRAL PANTEC, 2.5 T – TANDEM AXLE.....	27
2.2.26	WT UNBRAKED TANKER, 2400 LITRE “DIESEL”.....	28
2.2.27	WT ‘BRAKED’ TANKER, 2400 LITRE “DIESEL”.....	29
2.2.28	WT ‘UNBRAKED’ TANKER, 1200 LITRE “DIESEL”.....	30
2.2.29	WT ‘BRAKED’ TANKER, 1200 LITRE “DIESEL”.....	31
2.2.30	WT POLY WATER TANK TRAILERS.....	32
3	HORSE FLOATS	33
3.1	DOUBLE HORSE FLOATS.....	33
3.1.1	ECONOMY.....	33
3.1.2	S MODEL.....	34
3.1.3	SL MODEL.....	35
3.1.4	SLX MODEL.....	36
3.2	ANGLE LOAD HORSE FLOATS.....	37
3.2.1	2 HORSE.....	37
3.2.2	3 HORSE.....	38
3.2.3	4 HORSE.....	39
3.3	GOOSENECK TRAILERS.....	40
3.3.1	2.0 METRE WIDE ANGLE LOAD.....	40
3.3.2	2.46 METRE WIDE ANGLE LOAD.....	41



2 BOX (WT) TRAILERS

2.1 WT TRAILER TOPS

2.1.1 TOOLBOX TOP

<ul style="list-style-type: none"> ➤ Apex – 450 mm High ➤ Sides – 220 mm High ➤ Lift up Lid Each Side & Prop Support 	<ul style="list-style-type: none"> ➤ Lifting Handle on Door ➤ Chain Link Lock Points

2.1.2 FIBREGLASS

<ul style="list-style-type: none"> ➤ Rectangular Top approximately 450 mm High ➤ Front Hinge 	<ul style="list-style-type: none"> ➤ Gas Struts ➤ Foam Tap Seal

2.1.3 FLAT LID

<ul style="list-style-type: none"> ➤ Side Hinge ➤ RHS Frame, Flat Sheet 	<ul style="list-style-type: none"> ➤ Lockable ➤ Prop Up

2.1.4 PANTEC

<ul style="list-style-type: none"> ➤ Rectangular Top ➤ Lift Up Lid each Side & Propped ➤ Front & Rear Fixed Ladder Rack 	<ul style="list-style-type: none"> ➤ 'T' Handle Lock (two per side) ➤ Foam Tape Door Seal

2.1.5 TOURNEAU COVER

<ul style="list-style-type: none"> ➤ Round Bar Bow 	<ul style="list-style-type: none"> ➤ Black Vinyl Cover complete with Bungie Strap

2.1.6 TRADESMAN TOP

<ul style="list-style-type: none"> ➤ Apex 800 mm High (approximately) 	<ul style="list-style-type: none"> ➤ 900 mm Across Top (approximately)

2.1.7 WELDED MESH CAGE

<ul style="list-style-type: none"> ➤ Angle Frame ➤ 75 x 50 x 4 mm Mesh 	<ul style="list-style-type: none"> ➤ Rear Hinge Gate ➤ Removable Rear Bar



2.2 WT TRAILER TYPES

2.2.1 WT GENERAL PURPOSE

Sizing:	WT 00	1500 x 900 mm	(5 x 3)
	WT 01	1500 x 1070 mm	(5 x 3½)
	WT 02	1800 x 1200 mm	(6 x 4)
Structural Capacity:	600 kg		
Aggregate Trailer Mass (ATM):	600 kg		
Body:	Panels Flat 310 mm High Rear Tailgate		
Floor:	Flat 1.6 mm Sheet		
Chassis:	Drawbar	50 x 50 x 2 mm SHS	
	Cross Runner	35 x 35 x 2 mm RHS	
	Side Runner	35 x 35 x 2 mm	(1200 mm Long)
Tie Rail:	20 x 20 x 1.6 mm SHS Sides Only		
Corner Post:	50 x 50 x 2 mm Front Only		
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	3 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Wing Nuts to Secure Tailgate		
	Lights in Back Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Plug Holder		
	Spare Carrier		



2.2.2 WT MEDIUM DUTY

Sizing:	WT 03	1800 x 1200 mm	(6 x 4)
Structural Capacity:	780 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Flat 310 mm High Rear Tailgate		
Floor:	Flat 1.6 mm Sheet		
Chassis:	Drawbar	65 x 35 x 2 mm RHS	
	Cross Runner	35 x 35 x 2 mm SHS	(2)
	Side Runner	35 x 35 x 2 mm RHS	(Full Length)
Tie Rail:	20 x 20 x 1.6 mm SHS	Sides Only	
Corner Post:	50 x 50 x 2 mm	Front Only	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	4 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Rattle Tailgate Latches Lights in Rear Channel Wired to Australian Design Rules (ADR) Standards Plug Holder Spare Carrier		



2.2.3 WT HEAVY DUTY

Sizing:	WT 04	1800 x 1200 mm	(6 x 4)
	WT 07	2100 x 1200 mm	(7 x 4)
	WT 09	2400 x 1200 mm	(8 x 4)
	WT 11	2100 x 1500 mm	(7 x 5)
	WT 13	2400 x 1500 mm	(8 x 5)
Structural Capacity:	900 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Drawbar	65 x 35 x 2 mm RHS	
	Cross Runner	35 x 35 x 2 mm RHS	(6 x 4 – 2)
	Cross Runner	35 x 35 x 2 mm RHS	(Others – 3)
	Side Runner	35 x 35 x 2 mm	(Full Length)
	Front Cross Runner	35 x 35 x 2 mm	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear, Plastic Capped c/w Lock Bolt & Nut	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	5 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to Secure Tailgate		
	Lights in Rear Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Rear	Checker Plate Folded	
	Plug Holder		
Spare Carrier			



2.2.4 WT EXTRA HEAVY DUTY

Sizing:	WT 06	1800 x 1200 mm	(6 x 4)
	WT 08	2100 x 1200 mm	(7 x 4)
	WT 10	2400 x 1200 mm	(8 x 4)
	WT 12	2100 x 1500 mm	(7 x 5)
	WT 14	2400 x 1500 mm	(8 x 5)
Structural Capacity:	1100 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Drawbar	75 x 50 x 2 mm RHS	
	Cross Runner	50 x 50 x 2 mm RHS	(6 x 4 – 2)
	Cross Runner	50 x 50 x 2 mm RHS	(Others – 3)
	Side Runner	50 x 50 x 2 mm	(Full Length)
	Front Cross Runner	50 x 50 x 2 mm	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear, Plastic Capped c/w Lock Bolt & Nut	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres plus Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to Secure Tailgate		
	Lights in Rear Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Front & Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.5 WT EXTRA HEAVY DUTY HIGHSIDES

Sizing:	WT 111	1800 x 1200 mm	(6 x 4)
	WT 308	2100 x 1200 mm	(7 x 4)
	WT 310	2400 x 1200 mm	(8 x 4)
	WT 309	2100 x 1500 mm	(7 x 5)
	WT 433	2400 x 1500 mm	(8 x 5)
Structural Capacity:	1100 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Four Ribbed 510 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Drawbar	75 x 50 x 2 mm RHS	
	Cross Runner	50 x 50 x 2 mm RHS	(6 x 4 – 2)
	Cross Runner	50 x 50 x 2 mm RHS	(Others – 3)
	Side Runner	50 x 50 x 2 mm	(Full Length)
	Front Cross Runner	50 x 50 x 2 mm	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear, Plastic Capped c/w Lock Bolt & Nut	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres plus Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to Secure Tailgate		
	Lights in Rear Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Front & Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.6 WT HEAVY DUTY - GALVANISED

Sizing:	WT 936	1800 x 1200 mm	(6 x 4)
	WT 937	2100 x 1200 mm	(7 x 4)
	WT 938	2400 x 1200 mm	(8 x 4)
Structural Capacity:	900 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate		
Floor:	Flat 1.6 mm Galvanised Sheet		
Chassis:	Drawbar	75 x 50 x 2 mm RHS	
	Cross Runner	35 x 35 x 2 mm RHS	(6 x 4 – 2)
	Cross Runner	35 x 35 x 2 mm RHS	(Others – 3)
	Side Runner	35 x 35 x 2 mm	(Full Length)
	Front Cross Runner	35 x 35 x 2 mm	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear c/w Lock Bolt & Nut	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	5 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres		
Safety Chain:	8 mm Single		
Finish:	Hot Dipped Galvanised		
Common Articles:	Anti Luce Fasteners to Secure Tailgate		
	Lights in Rear Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.7 WT EXTRA HEAVY DUTY - GALVANISED

Sizing:	WT 05	1800 x 1200 mm	(6 x 4)
	WT 622	2100 x 1200 mm	(7 x 4)
	WT 939	2400 x 1200 mm	(8 x 4)
Structural Capacity:	1100 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Drawbar	75 x 50 x 2 mm RHS	
	Cross Runner	50 x 50 x 2 mm RHS	(6 x 4 – 2)
	Cross Runner	50 x 50 x 2 mm RHS	(Others – 3)
	Side Runner	50 x 50 x 2 mm	(Full Length)
	Front Cross Runner	50 x 50 x 2 mm	
	Floor Noggin	Angle	(8 x 5 Only)
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear c/w Lock Bolt & Nut	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti – Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15 " Second Hand Rims & Tyres		
Safety Chain:	8 mm Single		
Finish:	Hot Dipped Galvanised		
Common Articles:	Anti Luce Fasteners to Secure Tailgate		
	Lights in Rear Channel		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.8 WT 2 T TANDEM TRAILER

Sizing:	WT 18	2400 x 1500 mm	(8 x 5)
	WT 29	2400 x 1800 mm	(8 x 6)
	WT 20	2700 x 1500 mm	(9 x 5)
	WT 41	2700 x 1800 mm	(9 x 6)
	WT 22	3000 x 1800 mm	(10 x 6)
	WT 24	3600 x 1800 mm	(12 x 6)
Structural Capacity:	2000 kg		
Aggregate Trailer Mass (ATM):	2000 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate, Bar & Pipe Hinge 40 x 40 SHS Under Lip Front, Rear & Sides		
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	50 x 50 x 2 mm	
	Front Cross Runner	50 x 50 x 2 mm	
	Cross Runner	50 x 50 x 2 mm (5)	(8 x 5)
	Cross Runner	50 x 50 x 2 mm (6)	(9 x 5)
	Cross Runner	50 x 50 x 2 mm (7)	(10 x 6)
	Cross Runner	50 x 50 x 2 mm (8)	(12 x 6)
Drawbar	75 x 50 x 3 mm		
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear c/w Lock Bolt & Nut	
Axle:	45 mm Round Solid S1040		
Hubs & Bearings:	5 Stud SL		
Brakes:	9" Mechanical Override (1 Axle)		
Suspension:	4 Leaf 45 x 8 mm Shackle Rocker		
Coupling:	Mechanical Override 50 mm		
Wheels:	14" Second Hand Rims & LT Tyres plus Spare		
Safety Chain:	10 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to Secure Tailgate Lights in Rear Channel Multi-Volt L.E.D. Lights Mudguard Support Front & Rear Checker Plate Folded Plug Holder Spare Carrier 8" Swivel Jockey Wheel		



2.2.9 WT 2.5 T TANDEM TRAILER

Sizing:	WT 19	2400 x 1500 mm	(8 x 5)
	WT 42	2400 x 1800 mm	(8 x 6)
	WT 21	2700 x 1500 mm	(9 x 5)
	WT 43	2700 x 1800 mm	(9 x 6)
	WT 23	3000 x 1800 mm	(10 x 6)
	WT 25	3600 x 1800 mm	(12 x 6)
Structural Capacity:	2500 kg		
Aggregate Trailer Mass (ATM):	2500 kg		
Body:	Panels Three Ribbed 310 mm High Rear Tailgate, Bar & Pipe Hinge 40 x 40 SHS Under Lip Front, Rear & Sides		
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	50 x 50 x 3 mm	
	Front Cross Runner	50 x 50 x 3 mm	
	Cross Runner	50 x 50 x 2 mm (5)	(8 x 5)
	Cross Runner	50 x 50 x 2 mm (6)	(9 x 5)
	Cross Runner	50 x 50 x 2 mm (7)	(10 x 6)
	Cross Runner	50 x 50 x 2 mm (8)	(12 x 6)
Drawbar	100 x 50 x 3 mm		
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear c/w Lock Bolt & Nut	
Axle:	45 mm Round Solid S1040		
Hubs & Bearings:	5 Stud SL		
Brakes:	10" Electric Both Axles (In Cab) Battery Breakaway		
Suspension:	5 Leaf 45 x 8 mm Shackle Rocker Park Brake & Breakaway		
Coupling:	Electric Coupling 50 mm		
Wheels:	14" New Light Truck Tyres & Spare		
Safety Chain:	10 mm Double		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to Secure Tailgate Lights in Rear Channel Multi-Volt L.E.D. Lights Mudguard Support Front & Rear Plug Holder Spare Carrier 8" Swivel Jockey Wheel		
			Checker Plate Folded



2.2.10 WT 3 T TANDEM TRAILER

Sizing:	2400 x 1500 mm	(8 x 5)
	2400 x 1800 mm	(8 x 6)
	2700 x 1500 mm	(9 x 5)
	2700 x 1800 mm	(9 x 6)
	3000 x 1800 mm	(10 x 6)
	3600 x 1800 mm	(12 x 6)
Structural Capacity:	3000 kg	
Aggregate Trailer Mass (ATM):	3000 kg	
Body:	Panels Three Ribbed 310 mm High Rear Tailgate, Bar & Pipe Hinge 40 x 40 SHS Under Lip Front, Rear & Sides	
Floor:	Checker Plate 2.1 mm	
Chassis:	Side Runner	75 x 50 x 3 mm
	Front Cross Runner	70 x 50 x 3 mm
	Cross Runner	65 x 35 x 2 mm (5) (8 x 5)
	Cross Runner	65 x 35 x 2 mm (6) (9 x 5)
	Cross Runner	65 x 35 x 2 mm (7) (10 x 6)
	Cross Runner	65 x 35 x 2 mm (8) (12 x 6)
	Drawbar	100 x 50 x 3 mm
Tie Rail:	20 nb Pipe	Front, Rear & Sides
Corner Post:	50 x 50 x 2 mm c/w Lock Bolt & Nut	Front & Rear
Axle:	45 mm Round Solid S1040	
Hubs & Bearings:	5 Stud Ford	
Brakes:	10" Electric Both Axles (In Cab) Battery Breakaway	
Suspension:	6 Leaf 45 x 8 mm Shackle Rocker Park Brake & Breakaway	
Coupling:	Electric Coupling 50 mm	
Wheels:	14" Sunraysia New Light Truck Tyres & Spare	
Safety Chain:	10 mm Double	
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Anti Luce Fasteners to Secure Tailgate Lights in Rear Channel Multi-Volt L.E.D. Lights Mudguard Support Front & Rear Plug Holder Spare Carrier 8" Swivel Jockey Wheel	
		Checker Plate Folded



2.2.11 WT 3.5 T TANDEM TRAILER

Sizing:	2400 x 1500 mm	(8 x 5)
	2400 x 1800 mm	(8 x 6)
	2700 x 1500 mm	(9 x 5)
	2700 x 1800 mm	(9 x 6)
	3000 x 1800 mm	(10 x 6)
	3600 x 1800 mm	(12 x 6)
Structural Capacity:	3500 kg	
Aggregate Trailer Mass (ATM):	3500 kg	
Body:	Panels Three Ribbed 310 mm High Rear Tailgate, Bar & Pipe Hinge 40 x 40 SHS Under Lip Front, Rear & Sides	
Floor:	Checker Plate 2.1 mm	
Chassis:	Side Runner	75 x 50 x 3 mm
	Front Cross Runner	70 x 50 x 3 mm
	Cross Runner	65 x 35 x 2 mm (5) (8 x 5)
	Cross Runner	65 x 35 x 2 mm (6) (9 x 5)
	Cross Runner	65 x 35 x 2 mm (7) (10 x 6)
	Cross Runner	65 x 35 x 2 mm (8) (12 x 6)
	Drawbar	125 x 75 x 4 mm
Tie Rail:	20 nb Pipe	Front, Rear & Sides
Corner Post:	50 x 50 x 2 mm c/w Lock Bolt & Nut	Front & Rear
Axle:	50 mm Round Solid S1040 Parallel	
Hubs & Bearings:	6 Stud, Parallel	
Brakes:	10" Electric Both Axles (In Cab) Battery Breakaway	
Suspension:	8 Leaf 45 x 8 mm Shackle Rocker Park Brake & Breakaway	
Coupling:	Electric Coupling 50 mm	
Wheels:	16" New 205 Tyres & New Spare Sunraysia	
Safety Chain:	8 mm Hi-Tensile Double	
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Anti Luce Fasteners to Secure Tailgate Lights in Rear Channel Multi-Volt L.E.D. Lights Mudguard Support Front & Rear Plug Holder Spare Carrier 10" Extra Heavy Duty Swivel Jockey Wheel Checker Plate Folded	



2.2.12 WT CAR CARRIER, 2 T - LD

Sizing:	WT 707	4000 x 2000 mm	Tandem Axle
Structural Capacity:	2000 kg		
Aggregate Trailer Mass (ATM):	2000 kg		
Body:	Side Rail	50 x 25 x 2 mm	
Floor:	Two Tracks Checker Plate 600 mm		
Chassis:	Side Runner	75 x 50 x 3 mm	
	Front Cross Runner	70 x 50 x 3 mm	
	Rear Cross Runner	70 x 50 x 3 mm	
	Drawbar	75 x 50 x 3 mm	
	Floor Track Support	75 x 50 x 2 mm	
	Track Noggins	65 x 35 x 2 mm	
	Front Stop	75 x 50 x 2 mm	
Axle:	Independent Rubber Suspension		
Hubs & Bearings:	5 Stud LM		
Brakes:	10" Electric on One Axle (In Cab) Park Brake		
Suspension:	Independent Rubber Suspension		
Coupling:	Electric Brake Coupling 50 mm		
Wheels:	14" Rims & Tyres 2 nd Hand Light Truck plus Spare		
Safety Chain:	10 mm Double		
Ramps:	1500 x 400	Hook On, Angle Runners Ramps Stored between Floor Tracks	
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights on Rear Gusset Multi-Volt L.E.D. Lights Angle Mudguard Support Plug Holder Spare Carrier 8" Swivel Jockey Wheel		



2.2.13 WT CAR CARRIER, 2 T - TILT

Sizing:	WT 26	4000 x 2000 mm	Tandem Axle
Structural Capacity:	2000 kg		
Aggregate Trailer Mass (ATM):	2000 kg		
Body:	Side Rail	50 x 25 x 2 mm	
	U Bolt Tie Down Points		
	Winch	10:1 5:1 1:1 & Post	
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	75 x 50 x 3 mm	
	Front Cross Runner	75 x 50 x 3 mm	
	Rear Cross Runner	100 x 50 x 3 mm	
	Cross Runner	65 x 35 x 2 mm (6)	
	Drawbar	100 x 50 x 3 mm	
	Drawbar Tilt & Lock Down Pin		
	Drawbar Guide	65 x 35 x 2 mm	
	Front Stop	100 x 50 x 3 mm	
Axle:	45 mm Round Solid S1040		
Hubs & Bearings:	5 Stud SL		
Brakes:	10" Electric on One Axle (In Cab) Park Brake		
Suspension:	4 Leaf 45 x 8 mm Shackle Rocker		
Coupling:	Electric Brake Coupling 50 mm		
Wheels:	14" New Light Truck Tyres & Spare		
Safety Chain:	10 mm Double		
Ramps:	1200 x 600	Angle Runners, Hinged	
	Lynch Pin & Bullet	Lockable	
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights on Rear Gusset		
	Multi-Volt L.E.D. Lights		
	Angle Mudguard Support		
	Plug Holder		
	Spare Carrier		
	8" Swivel Jockey Wheel		



2.2.14 WT CAR CARRIER HD, 2.5 T - TILT

Sizing:	WT 28	4300 x 2000 mm	Tandem Axle
Structural Capacity:	2500 kg		
Aggregate Trailer Mass (ATM):	2500 kg		
Body:	Side Rail	50 x 25 x 3 mm	
	U Bolt Tie Down Points		
	Winch	10:1 5:1 1:1 & Post	
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	75 x 50 x 3 mm	
	Front Cross Runner	75 x 50 x 3 mm	
	Rear Cross Runner	100 x 50 x 3 mm	
	Cross Runner	65 x 35 x 2 mm (10)	
	Drawbar	100 x 50 x 3 mm	
	Front Stop	100 x 50 x 3 mm	
	Tilt off Drawbar		
Axle:	45 mm Round S/L		
Hubs & Bearings:	5 Stud SL		
Brakes:	10" Electric on Both Axles, Park Brake & Breakaway		
Suspension:	5 Leaf 45 x 8 mm Shackle Rocker		
Coupling:	Electric Brake Coupling 50 mm		
Wheels:	14" New Light Truck Tyres & Spare		
Safety Chain:	10 mm Double		
Ramps:	1200 x 600	Angle Runners, Hinged	Lynch Pin & Bullet Lockable
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights on Rear Gusset Multi-Volt L.E.D. Lights Angle Mudguard Support Plug Holder Spare Carrier 8" Swivel Jockey Wheel		



2.2.15 WT CAR CARRIER HD, 3 T - TILT

Sizing:	WT 288	5000 x 2000 mm	Tandem Axle
Structural Capacity:	3000 kg		
Aggregate Trailer Mass (ATM):	3000 kg		
Body:	Side Rail	50 x 25 x 2 mm	U Bolt Tie Down Points Winch Mount
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	75 x 50 x 3 mm	Front Cross Runner 75 x 50 x 3 mm Rear Cross Runner 125 x 75 x 4 mm Cross Runner 65 x 35 x 2 mm (10) Drawbar 125 x 75 x 4 mm Front Stop 100 x 50 x 3 mm Floor Noggins 50 x 50 x 5 mm Angle Tilt off Drawbar
Axle:	45 mm Square S/L		
Hubs & Bearings:	5 Stud SL		
Brakes:	10" Electric on Both Axles, Park Brake & Breakaway		
Suspension:	6 Leaf 45 x 8 mm Shackle Rocker		
Coupling:	Electric Brake Coupling 50 mm		
Wheels:	14" New Light Truck Tyres & Spare (Sunraysia)		
Safety Chain:	10 mm Double		
Ramps:	1500 x 600	Angle Runners, Hinged Lynch Pin & Bullet Lockable	
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights on Rear Gusset Multi-Volt L.E.D. Lights Angle Mudguard Support Plug Holder Spare Carrier 8" Heavy Duty Swivel Jockey Wheel		



2.2.16 WT CAR CARRIER HD, 3.5 T - TILT

Sizing:	WT 289	5200 x 2000 mm	Tandem Axle
Structural Capacity:	3500 kg		
Aggregate Trailer Mass (ATM):	3500 kg		
Body:	Side Rail	50 x 25 x 2 mm	U Bolt Tie Down Points Winch Mount
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	75 x 50 x 3 mm	Front Cross Runner 75 x 50 x 3 mm Rear Cross Runner 125 x 75 x 4 mm Cross Runner 65 x 35 x 2 mm (10) Drawbar 125 x 75 x 4 mm Front Stop 100 x 50 x 3 mm Floor Noggins 50 x 50 x 5 mm Angle Tilt off Drawbar
Axle:	50 mm Round ESS 2 T		
Hubs & Bearings:	6 Stud ESS		
Brakes:	10" Electric on Both Axles, Park Brake & Breakaway		
Suspension:	8 Leaf 45 x 8 mm Shackle Rocker		
Coupling:	Electric Brake Coupling 50 mm		
Wheels:	14" 6 Stud New Light Truck Tyres & Spare (Sunraysia)		
Safety Chain:	Hi Tensile & Bergloc		
Ramps:	1500 x 600	Angle Runners, Hinged	Lynch Pin & Bullet Lockable
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights on Rear Gusset Multi-Volt L.E.D. Lights Angle Mudguard Support Plug Holder Spare Carrier 10" Extra Heavy Duty Swivel Jockey Wheel		



2.2.17 WT OFF ROAD TOURER

Sizing:	WT 15	1800 x 1200 mm	(6 x 4)
	WT 16	2100 x 1200 mm	(7 x 4)
Structural Capacity:	1100 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Four Ribbed 510 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	50 x 50 x 2 mm	
	Front Cross Runner	50 x 50 x 2 mm	
	Rear Cross Runner	75 x 50 x 2 mm	
	Cross Runner	50 x 50 x 2 mm	
	Drawbar	75 x 50 x 3 mm – Ext. To 1800 F-F	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front & Rear c/w Lock Bolt & Nut	
Axle:	45 mm Round Solid S1040		
Hubs & Bearings:	6 Stud SL		
Suspension:	4 Leaf 45 x 8 mm Shackle Springs		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	16" 6 Stud Landcruiser 2 nd Hand & Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to secure Tailgate Lights on Rear Gusset Wired to Australian Design Rules (ADR) Standards Mudguard Support Front & Rear Checker Plate Folded Plug Holder Spare Carrier 6" Swivel Jockey Wheel		



2.2.18 WT OFF ROAD GRAND TOURER

Sizing:	WT 820	1800 x 1200 mm	(6 x 4)
	WT 821	2100 x 1200 mm	(7 x 4)
Structural Capacity:	1300 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Panels Four Ribbed 510 mm High Rear Tailgate		
Floor:	Checker Plate 2.1 mm		
Chassis:	Side Runner	50 x 50 x 3 mm	
	Front Cross Runner	50 x 50 x 3 mm	
	Rear Cross Runner	75 x 50 x 3 mm	
	Cross Runner	50 x 50 x 2 mm	
	Drawbar	75 x 50 x 3 mm – Ext. To 1800 F-F	
	Drawbar Webb	14 mm Round Bar	
Tie Rail:	20 nb Pipe	Front, Rear & Sides	
Corner Post:	50 x 50 x 2 mm	Front Only	
Axle:	45 mm Square Parallel S1040		
Hubs & Bearings:	6 Stud ESS		
Suspension:	6 Leaf 60 x 7 mm Outback Long Shackle		
Coupling:	360° Poly Block or Ball Coupling		
Wheels:	16" 6 Stud Sunraysia, 2 nd Hand Tyres & Spare		
Safety Chain:	10 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Anti Luce Fasteners to secure Tailgate Lights on Rear Gusset Wired to Australian Design Rules (ADR) Standards Mudguard Support Front & Rear Checker Plate Folded Plug Holder Vertical Spare Carrier Encased Wiring 8" Swivel Jockey Wheel Provision for Tool Box		



2.2.19 WT GOLF BUGGY, OPEN

Sizing:	WT 17	2400 x 1400 mm
Structural Capacity:	780 kg	
Aggregate Trailer Mass (ATM):	750 kg	
Body:	Floor Tracks	Checker Plate 400 mm Wide
	Front & Side Rails	50 x 25 x 2 mm
	5 x U Bolt Tie Up Points	
Chassis:	Side Runner	35 x 35 x 2 mm
	Front Cross Runner	35 x 35 x 2 mm
	Rear Cross Runner	75 x 50 x 2 mm
	Drawbar	65 x 35 x 2 mm
	Tilt off Drawbar	Lynch Pin Lock Down
Axle:	39 mm Round Solid S1040	
Hubs & Bearings:	5 Stud LM	
Suspension:	2 Leaf 45 x 8 mm Slipper	
Coupling:	Quick Release 50 mm Adjustable	
Wheels:	10" 5 Stud Alloy & Spare – NEW	
Safety Chain:	8 mm Single	
Ramps:	600 x 400	Checker Plate Hinged Ramps (1 Pair)
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Lights on Rear Gusset	
	Mudguard Support Front & Rear	Checker Plate Folded
	Plug Holder	
	Spare Carrier	
	6" Swivel Jockey Wheel	



2.2.20 WT GOLF BUGGY, ENCLOSED

Sizing:	WT 698	2400 x 1400 mm
Structural Capacity:	780 kg	
Aggregate Trailer Mass (ATM):	750 kg	
Body:	Full Checker Plate Floor Side Panels 1.6 mm 230 mm High Flat Front Panel 1.6 mm 150 mm High Side Tie Rail 20 nb Pipe	
Chassis:	Side Runner 35 x 35 x 2 mm Front Cross Runner 35 x 35 x 2 mm Cross Runner 35 x 35 x 2 mm (3) Rear Cross Runner 75 x 50 x 2 mm Drawbar 65 x 35 x 2 mm Tilt off Drawbar Lynch Pin Lock Down	
Axle:	39 mm Round Solid S1040	
Hubs & Bearings:	5 Stud LM	
Suspension:	2 Leaf 45 x 8 mm Slipper	
Coupling:	Quick Release 50 mm Adjustable	
Wheels:	10" 5 Stud Alloy – NEW plus Spare	
Safety Chain:	8 mm Single	
Ramps:	600 x 400 Checker Plate Hinged Ramps (1 Pair) Checker Plate Infill between	
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Lights on Rear Gusset Mudguard Support Front & Rear Checker Plate Folded Plug Holder Spare Carrier 6" Swivel Jockey Wheel	



2.2.21 WT MOTORBIKE TRAILER

Sizing:	WT 891	2100 x 1200 mm	(1 Bike)
	WT 892	2100 x 1200 mm	(2 Bike)
	WT 893	2400 x 1500 mm	(3 Bike)
Structural Capacity:	1000 kg		
Aggregate Trailer Mass (ATM):	750 kg		
Body:	Checker Plate Floor & Front Wheel Support Light Gussets Mudguards		
Chassis:	Side Runner	50 x 50 x 2 mm	
	Cross Runner	50 x 50 x 2 mm (2)	
	Rear Cross Runner	50 x 50 x 2 mm	
	Drawbar	75 x 50 x 2 mm RHS	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" / 15" Second Hand Rims & Tyres plus Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Hook On Ramp Checker Plate		
	U Bolt Tie Downs		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Front & Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		
Ramp Storage Under Floor			



2.2.22 WT INTEGRAL PANTEC, 1200 mm HIGH, SINGLE AXLE

Sizing:	WT 346-12	1800 x 1200 mm	(6 x 4)
	WT 347-12	2100 x 1200 mm	(7 x 4)
	WT 348-12	2100 x 1500 mm	(7 x 5)
	WT 349-12	2400 x 1200 mm	(8 x 4)
	WT 350-12	2400 x 1500 mm	(8 x 5)
Height:	1200 mm	(4 ft)	
Gross Trailer Mass (GTM):	750 kg		
Body:	Checker Plate Floor Zinc Sheeting RHS Frame		
Rear Doors:	4 ft Wide	Single Side Hinge	
	5 ft Wide	Double Side Hinge	
Chassis:	Side Runner	50 x 50 x 2 mm (Full Length)	
	Front Cross Runner	50 x 50 x 2 mm	
	Rear Cross Runner	75 x 50 x 3 mm	
	Cross Runner	50 x 50 x 2 mm (6 x 4 - 2)	
	Cross Runner	50 x 50 x 2 mm (Others - 3)	
	Drawbar	75 x 50 x 3 mm RHS	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti-Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" Second Hand Rims & Tyres plus Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights in Gussets		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Front & Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.23 WT INTEGRAL PANTEC, 1500 mm HIGH, SINGLE AXLE

Sizing:	WT 346-15	1800 x 1200 mm	(6 x 4)
	WT 347-15	2100 x 1200 mm	(7 x 4)
	WT 348-15	2100 x 1500 mm	(7 x 5)
	WT 349-15	2400 x 1200 mm	(8 x 4)
	WT 350-15	2400 x 1500 mm	(8 x 5)
Height:	1500 mm	(5 ft)	
Gross Trailer Mass (GTM):	750 kg		
Body:	Checker Plate Floor Zinc Sheeting RHS Frame		
Rear Doors:	4 ft Wide	Single Side Hinge	
	5 ft Wide	Double Side Hinge	
Chassis:	Side Runner	50 x 50 x 2 mm (Full Length)	
	Front Cross Runner	50 x 50 x 2 mm	
	Rear Cross Runner	75 x 50 x 3 mm	
	Cross Runner	50 x 50 x 2 mm (6 x 4 - 2)	
	Cross Runner	50 x 50 x 2 mm (Others - 3)	
	Drawbar	75 x 50 x 3 mm RHS	
Axle:	39 mm Round Solid S1040		
Hubs & Bearings:	5 Stud LM		
Suspension:	6 Leaf 45 x 6 mm Slipper (Anti-Rattle)		
Coupling:	Quick Release 50 mm Adjustable		
Wheels:	14" Second Hand Rims & Tyres plus Spare		
Safety Chain:	8 mm Single		
Finish:	Etch Prime & Enamel Top Coat		
Common Articles:	Lights in Gussets		
	Wired to Australian Design Rules (ADR) Standards		
	Mudguard Support Front & Rear	Checker Plate Folded	
	Plug Holder		
	Spare Carrier		
	6" Swivel Jockey Wheel		



2.2.24 WT INTEGRAL PANTEC, 2 T – TANDEM AXLE

Sizing:	2400 x 1500 mm (8 x 5)	
Height:	1200 mm (4 ft)	
	1500 mm (5 ft)	
Aggregate Trailer Mass (ATM):	2000 kg	
Body:	Checker Plate Floor Zinc Sheeting RHS Frame	
Rear Doors:	Double Side Hinge	
Chassis:	Side Runner	50 x 50 x 2 mm
	Front Cross Runner	50 x 50 x 2 mm
	Rear Cross Runner	75 x 50 x 3 mm
	Cross Runner	50 x 50 x 2 mm
	Drawbar	100 x 50 x 3 mm
Axle:	45 mm Round Solid S1040	
Hubs & Bearings:	5 Stud SL	
Suspension:	4 Leaf 45 x 8 mm Shackle Rocker	
Coupling:	Mechanical Override 50 mm	
Wheels:	14" Second Hand Rims & Tyres plus Spare	
Safety Chain:	10 mm Single	
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Lights in Gussets	
	Multi-Volt L.E.D. Lights	
	Mudguard Support Front & Rear	Checker Plate Folded
	Plug Holder	
	Spare Carrier	
	8" Swivel Jockey Wheel	



2.2.25 WT INTEGRAL PANTEC, 2.5 T – TANDEM AXLE

Sizing:	2400 x 1500 mm (8 x 5)	
Height:	1200 mm (4 ft)	
	1500 mm (5 ft)	
Aggregate Trailer Mass (ATM):	2500 kg	
Body:	Checker Plate Floor Zinc Sheeting RHS Frame	
Rear Doors:	Double Side Hinge	
Chassis:	Side Runner	50 x 50 x 3 mm
	Front Cross Runner	50 x 50 x 3 mm
	Rear Cross Runner	75 x 50 x 3 mm
	Cross Runner	50 x 50 x 2 mm
	Drawbar	100 x 50 x 3 mm
Axle:	45 mm Round Solid S1040	
Hubs & Bearings:	5 Stud SL	
Suspension:	6 Leaf 45 x 8 mm Shackle Rocker	
	Park Brake & Breakaway	
Coupling:	10" Electric both Axles (In Cab)	
	Battery Breakaway	
Wheels:	14" New Light Truck Tyres & 2 nd Hand Spare	
Safety Chain:	10 mm Double	
Finish:	Etch Prime & Enamel Top Coat	
Common Articles:	Lights in Gussets	
	Multi-Volt L.E.D. Lights	
	Mudguard Support Front & Rear	Checker Plate Folded
	Plug Holder	
	Spare Carrier	
	8" Swivel Jockey Wheel	



2.2.26 WT UNBRAKED TANKER, 2400 LITRE "DIESEL"

Aggregate Trailer Mass (ATM):	3000 kg
Body:	<p>Tank Cylinder 3 mm Rolled Plate & Dished Ends Internal Half Baffle Drum Rack on Drawbar</p> <ul style="list-style-type: none"> • Checker Plate Floor • RHS Frame <p>Tandem Axle Checker Plate Mudguards Front & Rear Checker Plate Mudguard Step Passenger Side Handle Vertical Spare Wheel Carrier on Drawbar Top Mounted Lifting Lug Points Tank Fittings</p> <ul style="list-style-type: none"> • 1" Breather • 2" Filler • 2" Outlet (Top Rear) • 1" Outlet x 2 (Ends at Bottom) • 1" Drain & Plug
Chassis:	<p>Drawbar 100 x 50 x 4 mm RHS Side Frame 150 x 150 x 10 mm Angle</p>
Fuel Capacity:	2400 Litre Maximum
Axle:	45 mm Square Slimline – 1600 kg
Hubs & Bearings:	6 Stud Landcruiser – Lazy
Suspension:	6 Leaf 45 x 8 mm Shackle Rocker
Coupling:	3.5 T 50 mm Ball
Wheels:	16" 6 Stud Sunraysia Landcruiser 2 nd Hand plus Spare
Safety Chain:	10 mm Double
Jockey Wheel:	8" Swivel
Finish:	Etch Prime & Hammer tone Charcoal Top Coat (Other Colours – P.O.A.)



2.2.27 WT 'BRAKED' TANKER, 2400 LITRE "DIESEL"

Aggregate Trailer Mass (ATM):	3000 kg
Body:	<p>Tank Cylinder 3 mm Rolled Plate & Dished Ends Internal Half Baffle Drum Rack on Drawbar</p> <ul style="list-style-type: none"> • Checker Plate Floor • RHS Frame <p>Tandem Axle Checker Plate Mudguards Front & Rear Checker Plate Mudguard Step Passenger Side Handle Vertical Spare Wheel Carrier on Drawbar Top Mounted Lifting Lug Points Tank Fittings</p> <ul style="list-style-type: none"> • 1" Breather • 2" Filler • 2" Outlet (Top Rear) • 1" Outlet x 2 (Ends at Bottom) • 1" Drain & Plug
Chassis:	<p>Drawbar 100 x 50 x 4 mm RHS Side Frame 150 x 150 x 10 mm Angle</p>
Fuel Capacity:	2400 Litre Maximum
Electrics:	Multi-Volt L.E.D. Lights
Axle:	45 mm Square Slimline – 1600 kg
Brakes:	10" Electric – 4 Wheel (In Cab Control) Park Brake / Battery Breakaway
Suspension:	6 Leaf 45 x 8 mm Shackle Rocker
Coupling:	3.5 T 50 mm Ball
Wheels:	14" Ford Sunraysia c/w New Light Truck Tyres plus Spare
Safety Chain:	10 mm Double
Jockey Wheel:	8" Swivel
Finish:	Etch Prime & Hammer tone Charcoal Top Coat (Other Colours – P.O.A.)



2.2.28 WT 'UNBRAKED' TANKER, 1200 LITRE "DIESEL"

Aggregate Trailer Mass (ATM):	1700 kg
Body:	<p>Tank Cylinder 3 mm Rolled Plate & Dished Ends Drum Rack on Drawbar</p> <ul style="list-style-type: none"> • Checker Plate Floor • RHS Frame <p>Single Axle Checker Plate Mudguards Front & Rear Checker Plate Mudguard Step Passenger Side Handle Vertical Spare Wheel Carrier on Drawbar Top Mounted Lifting Lug Points Tank Fittings</p> <ul style="list-style-type: none"> • 1" Breather • 2" Filler • 2" Outlet (Top Rear) • 1" Outlet x 2 (Ends at Bottom) • 1" Drain & Plug
Chassis:	<p>Drawbar 100 x 50 x 4 mm RHS Side Frame 150 x 150 x 10 mm Angle</p>
Fuel Capacity:	1200 Litre Maximum
Axle:	45 mm Square Slimline
Suspension:	8 Leaf 45 x 8 mm Shackle
Coupling:	3.5 T 50 mm Ball
Wheels:	16" 6 Stud Sunraysia, 2 nd Hand Tyres & Spare Wheel
Safety Chain:	10 mm Double
Jockey Wheel:	8" Swivel
Finish:	Etch Prime & Hammer tone Charcoal Top Coat (Other Colours – P.O.A.)



2.2.29 WT 'BRAKED' TANKER, 1200 LITRE "DIESEL"

Aggregate Trailer Mass (ATM):	1700 kg
Body:	<p>Tank Cylinder 3 mm Rolled Plate & Dished Ends Drum Rack on Drawbar</p> <ul style="list-style-type: none"> • Checker Plate Floor • RHS Frame <p>Single Axle Checker Plate Mudguards Front & Rear Checker Plate Mudguard Step Passenger Side Handle Vertical Spare Wheel Carrier on Drawbar Top Mounted Lifting Lug Points Tank Fittings</p> <ul style="list-style-type: none"> • 1" Breather • 2" Filler • 2" Outlet • 1" Outlet x 2 (Ends at Bottom) • 1" Drain & Plug
Chassis:	<p>Drawbar 100 x 50 x 4 mm RHS Side Frame 150 x 150 x 10 mm Angle</p>
Fuel Capacity:	1200 Litre Maximum
Electrics:	Multi-Volt L.E.D. Lights
Axle:	45 mm Square Slimline
Brakes:	10" Electric (In Cab Control) Park Brake
Suspension:	8 Leaf 45 x 8 mm Shackle
Coupling:	3.5 T 50 mm Ball
Wheels:	14" Ford Sunraysia c/w New Light Truck Tyres & Spare
Safety Chain:	10 mm Double
Jockey Wheel:	8" Swivel
Finish:	Etch Prime & Hammer tone Charcoal Top Coat (Other Colours – P.O.A.)



2.2.30 WT POLY WATER TANK TRAILERS

Sizing:	WT 0127	1000 Litre	2100 x 1300 mm S/Axle	ATM 1500 kg
	WT 0128	1500 Litre	2500 x 1500 mm T/Axle	ATM 2000 kg
	WT 0129	2000 Litre	2700 x 1500 mm T/Axle	ATM 2500 kg
	WT 0130	2500 Litre	2700 x 1500 mm T/Axle	ATM 3000 kg
	WT 0131	3000 Litre	3000 x 1600 mm T/Axle	ATM 3800 kg
Body:	Tank Mount <ul style="list-style-type: none"> • RHS • Locking Pins Mudguards c/w Front & Rear Supports Rear Back Channel Encase Wiring in SHS Platform at Front <ul style="list-style-type: none"> • Angle Frame • Checker Plate Lay Flat Spare Carrier on Drawbar			
Chassis:	RHS			
Axle & Bearings:	Single Axle	45 Round S/L c/w 10" Electric		
	Tandem Axle 2 T	45 Round S/L c/w 10" Electric (1)		
	Tandem Axle 2.5 T & 3 T	45 Round S/L c/w 10" Electric (2)		
	Tandem Axle 3.8 T	45 SQ Parallel 10" Electric (2)		
Suspension:	Single Axle	Shackle		
	Tandem Axle	Shackle Rocker		
Tank:	Poly Lid 2" Outlet at Bottom			
Coupling:	Up to 3 T	50 mm Round		
	3.8 T – 6 T	75 mm Ring		
Wheels:	Single Axle	14" 5 Stud Sunraysia Ford New Light Truck		
	Tandem Axle 2 T – 3 T	14" 5 Stud Sunraysia Ford New Light Truck		
	Tandem Axle 3.5 T	16" 6 Stud Sunraysia New Tyres		
Electrics:	Multi-Volt L.E.D. Lights			
Brake Kit:	1.5 T – 2 T	Park Brake		
	2.5 T – 3.8 T	Park Brake & Battery Breakaway		
Jockey Wheel:	1.5 T – 2.5 T	8" Swivel		
	3.8 T	8" Heavy Duty Swivel		
Safety Chain:	Single Axle	10 mm Single		
	Tandem Axle	10 mm Double		
Finish:	Hot Dipped Galvanised			



3 HORSE FLOATS

3.1 DOUBLE HORSE FLOATS

3.1.1 ECONOMY

Sizing:	3300 mm x 1670 mm x 2100 mm (11 Foot)
Bay Length:	1900 mm
Approx TARE Weight:	800 kg
Aggregate Trailer Mass (ATM):	2000 kg
Standard Inclusions:	<ul style="list-style-type: none"> • Two Wheel Electric Brakes • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • Two Pac White Paint • 2" & 1" Striping or Scrollwork
Economy Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Full Rubber Flooring • Removable Chest Bars, Head & Centre Divider • Rump Chains • 2 x Side Pads • Small Front Window • Side Access Door • Wheels 14" Ford 2nd Hand • 5 x 2nd Hand Light Truck Tyres / Wheel Covers • 8" Swivel Jockey Wheel & Clamp



3.1.2 S MODEL

Sizing:	3300 mm x 1670 mm x 2100 mm (11 Foot)
Bay Length:	1900 mm
Approx TARE Weight:	820 kg
Aggregate Trailer Mass (ATM):	2000 kg
Standard Inclusions:	<ul style="list-style-type: none"> • Two Wheel Electric Brakes • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • Two Pac White Paint • 2" & 1" Striping or Scrollwork • Multi-Volt L.E.D. Lights
S Model Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Full Rubber Flooring • Removable Chest Bars, Head & Centre Divider • Rump Bars at Rear • 2 x Side Pads • Large Front Window • Side Access Door • 400 mm Alloy Tread Plate Stone Guard and Front of Guards • 5 x New White 14" Ford Sunraysia Rims / 4 x New Light Truck Tyres / 2nd Hand Light Truck Spare • 8" Swivel Jockey Wheel & Clamp

3.1.3 SL MODEL

Sizing:	3300 mm x 1670 mm x 2100 mm (11 Foot)
Bay Length:	1900 mm
Approx TARE Weight:	840 kg
Aggregate Trailer Mass (ATM):	2000 kg
Standard Inclusions:	<ul style="list-style-type: none"> • Two Wheel Electric Brakes • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • Two Pac White Paint • 2" & 1" Striping or Scrollwork • Multi-Volt L.E.D. Lights
SL Model Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Full Rubber Flooring • Removable Chest Bars, Head & Centre Divider • Rump Bars at Rear • Fully Padded (Except Rump) • Interior Light • Kickboards • Large Front Window • Side Access Door • 600 mm Alloy Tread Plate Stone Guard and Front of Guards • 5 x New White 14" Ford Sunraysia Rims / 5 x New Light Truck Tyres • 8" Swivel Jockey Wheel & Clamp



3.1.4 SLX MODEL

Sizing:	3300 mm x 1670 mm x 2100 mm (11 Foot)
Bay Length:	1900 mm
Approx TARE Weight:	860 kg
Aggregate Trailer Mass (ATM):	2000 kg
Standard Inclusions:	<ul style="list-style-type: none"> • Two Wheel Electric Brakes • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • Two Pac White Paint • 2" & 1" Striping or Scrollwork • Multi-Volt L.E.D. Lights
SLX Inclusions:	<ul style="list-style-type: none"> • Enclosed 2 x Sliding Windows (Open at Rear) • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Full Rubber Flooring • Removable Chest Bars, Head & Centre Divider • Stallion Divider • Rump Bars at Rear • Fully Padded (Except Rump) • Interior Light • Kickboards • Large Front Window • 2 x Side Access Doors • 600 mm Alloy Tread Plate Stone Guard and Front of Guards • 5 x New White 14" Ford Sunraysia Rims / 5 x New Light Truck Tyres • 8" Swivel Jockey Wheel & Clamp



3.2 ANGLE LOAD HORSE FLOATS

3.2.1 2 HORSE

Sizing:	3200 mm x 2000 mm x 2100 mm (11 Foot)
Bay Length:	2500 mm
Approx TARE Weight:	980 kg
Aggregate Trailer Mass (ATM):	2000 kg
Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Removable Divider System (Built in Head Dividers) • Rump Padding • Interior Light • Kickboards • Large Front Window • Side Access Door • 600 mm Alloy Tread Plate Stone Guard and Front of Guards • 8" Swivel Jockey Wheel & Clamp • Multi-Volt L.E.D. Lights • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • Two Wheel Electric Brakes • 5 x New White 14" Ford Sunraysia Rims / 5 x New 185R14 Light Truck Tyres • 2" & 1" Striping or Scrollwork • Two Pac White Paint



3.2.2 3 HORSE

Sizing:	4200 mm x 2000 mm x 2100 mm	(14 Foot)
Bay Length:	2500 mm	
Approx TARE Weight:	1420 kg	
Aggregate Trailer Mass (ATM):	3300 kg	
Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Removable Divider System (Built in Head Dividers) • Rump Padding • Interior Light • Kickboards • Large Front Window • Side Access Door • 600 mm Alloy Tread Plate Stone Guard and Front of Guards • 8" Swivel Jockey Wheel & Clamp • Multi-Volt L.E.D. Lights • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • 10" Electric Brakes (1.8 T / Axle Parallel Bearings) • 16" 6 Stud White Sunraysia Wheels, c/w 205R16 New Tyres plus Spare • 2" & 1" Striping or Scrollwork • Two Pac White Paint 	



3.2.3 4 HORSE

Sizing:	5800 mm x 2000 mm x 2100 mm	(19 Foot)
Bay Length:	2500 mm	
Approx TARE Weight:	1550 kg	
Aggregate Trailer Mass (ATM):	3500 kg	
Inclusions:	<ul style="list-style-type: none"> • Open Sided • One Piece Spring Assisted Tailgate • Colourbond Sheet Finish on Tailgate • Removable Divider System (Built in Head Dividers) • Rump Padding • Interior Light • Kickboards • Large Front Window • Side Access Door • 600 mm Alloy Tread Plate Stone Guard and Front of Guards • 8" HD Swivel Jockey Wheel & Clamp • Multi-Volt L.E.D. Lights • Independent Suspension – 5 Year Warranty • Quality Galvanised Steel Chassis & Frame • Full Zinc Sheet Throughout (Rust Resistant) • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • One Piece Fibreglass Roof • 10" Electric Brakes (1.8 T / Axle Parallel Bearings) • 16" 6 Stud White Sunraysia Wheels, c/w 225R16 New Tyres plus Spare • 2" & 1" Striping or Scrollwork • Two Pac White Paint 	



3.3 GOOSENECK TRAILERS

3.3.1 2.0 METRE WIDE ANGLE LOAD

Sizing / TARE Weight / Aggregate Trailer Mass (ATM):	3 Horse	6600 mm x 2000 mm	TARE 1.7 T	ATM	3.5 T
	4 Horse	7600 mm x 2000 mm	TARE 1.9 T	ATM	4.0 T
	5 Horse	8600 mm x 2000 mm	TARE 2.1 T	ATM	4.49 T
	6 Horse	9600 mm x 2000 mm	TARE 2.3 T	ATM	4.49 T
Standard Inclusions:	<ul style="list-style-type: none"> • Open Sides • Spring Loaded Tailgate • Zincanneal Sheet Metal Panels, Fully Welded • Quality Galvanised Steel Chassis & Frame • One Piece Fibreglass Roof • Fully Removable Divider System, Head Dividers on All Dividers • Kickboards on Both Sides of the Float • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • 4 Wheel, Electric Brakes with a Breakaway System • 9 Tonne Coupling & Ball • Side Wind Jack • 12 Volt Internal Lights • 5 x 16" 6 Stud Wheels, New Tyres • Multi-Volt L.E.D. Lights & Clear Light • Colourbond Sheet Finish on Tailgate • Rump Padding • Alloy Tread Plate Stone Guard and Front of Guards • 2" & 1" Striping or Scrollwork • Side Access Door • 12 Months Warranty • Rubber Suspension with 5 Year Warranty (Up to ATM 4.49 T) • Two Pac White Paint 				
Wheels & Brakes:	3 & 4 Horse	16" 6 Stud Sunraysia c/w 225R16 Tyres 10" Electric 4 Wheel			
	5 & 6 Horse	16" 6 Stud Sunraysia c/w 235R16 Tyres 12" Electric 4 Wheel			



3.3.2 2.46 METRE WIDE ANGLE LOAD

Sizing:	<ul style="list-style-type: none"> • Sized to Suit Your Needs (ATM 3.5 T to 8.4 T) • Wheels Inside or Wheels Under 								
Standard Inclusions:	<ul style="list-style-type: none"> • Open Sides • Spring Loaded Tailgate • Zincanneal Sheet Metal Panels, Fully Welded • Quality Galvanised Steel Chassis & Frame • One Piece Fibreglass Roof • Removable Divider System complete with Head Divider • Kickboards on Both Sides of the Float • 17 mm Structural Hardwood Ply F27 Flooring • Sealed Insertion Rubber Matting • Load Sharing Suspension • Scam Air Brakes for Goosenecks over ATM 4.49 T • 9 Tonne Coupling & Ball • Side Wind Jack • 12 Volt Internal Lights • Multi-Volt L.E.D. Lights & Clear Light • Colourbond Sheet Finish on Tailgate • Rump Padding • 2" & 1" Striping or Scrollwork • Side Access Door • 12 Months Warranty • Two Pac White Paint <p>For more optional extras to customise your Gooseneck please visit our website www.mcneilltrailers.com</p>								
Wheels & Tyres:	<table border="0"> <tr> <td data-bbox="561 1361 715 1397">3.5 T – 4.0 T</td> <td data-bbox="756 1361 1225 1397">16" 6 Stud Sunraysia c/w 225R16 Tyres</td> </tr> <tr> <td></td> <td data-bbox="756 1397 1098 1433">10" Electric Brakes 4 Wheels</td> </tr> <tr> <td data-bbox="561 1469 641 1505">4.49 T</td> <td data-bbox="756 1469 1225 1505">16" 6 Stud Sunraysia c/w 235R16 Tyres</td> </tr> <tr> <td></td> <td data-bbox="756 1505 1002 1541">12" Electric 4 Wheel</td> </tr> </table>	3.5 T – 4.0 T	16" 6 Stud Sunraysia c/w 225R16 Tyres		10" Electric Brakes 4 Wheels	4.49 T	16" 6 Stud Sunraysia c/w 235R16 Tyres		12" Electric 4 Wheel
3.5 T – 4.0 T	16" 6 Stud Sunraysia c/w 225R16 Tyres								
	10" Electric Brakes 4 Wheels								
4.49 T	16" 6 Stud Sunraysia c/w 235R16 Tyres								
	12" Electric 4 Wheel								